

Return pulley and polyester strap

■ Opening return pulley

- The valve mechanism allows an easy cable insertion
- Rotating high-resistance hook
- With latch hook
- Only for steel cable



Return pulley with valve	80 kN POU00015	140 kN POU00016
Ø pulley (mm)	140	140
Ø cable (mm)	12	14
Weight (kg)	6,5	8,5

■ Aluminium return pulley

- Suitable for steel cables and polyester straps
- Rotating lock
- With ball bearing
- Lightness from aluminium
- Rotating flange

Aluminium return pulley	110 kN POU00055	150 kN POU00056	170 kN POU00057
Ø and width of pulley (mm)	158-35	198-42	198-42
Ø cable (mm)	14	16	16
Weight (kg)	2,4	3,9	5,1




■ Polyester strap

- Reinforced curls ends according to EN 1492-1
- Low friction
- No swelling in high humidity
- Polyester doubled for maximum strength

Polyester strip with 2 curve ends			
	Color code	Width	Length
SAN00010	Green	60 mm	3 m
SAN00011	Yellow	90 mm	3 m
SAN00012	Grey	120 mm	3 m

indications of resistance by the number of stripes and by the colour



Break point coef.7	Colour code	100%	80%	200%
14 000 kg	Green	2000 kg	1600 kg	4000 kg
21 000 kg	Yellow	3000 kg	2400 kg	6000 kg
28 000 kg	Grey	4000 kg	3200 kg	8000 kg

Curve ends

Indication of resistance by the colour

Indication of resistance by the number of stripes

