

■ Band-saw - RB series

3 wheel sizes for this band-saw, working with precision and robustness.

- Cutting precision with double blade brass guiding system (*up and down*)
- Cast iron wheel for better cutting line
- Cork seal on wheel for a better guidance
- All PTO driven models are equipped with a safety lever to release
- Blade included
- Belt driven
- Blade tension indicator



RB 620 PET

Band-saw	RB 520M	RB 520T	RB 620M	RB 620T	RB 620P	RB620PEM	RB620PET	RB 720T	RB 720P	RB 720PET
Power supply	230 V 2,2 kW	400 V 2,2 kW	230 V 2,2 kW	400 V 2,2 kW	PTO tractor	PTO + Elec. 230V - 2.2kW	PTO + Elec. 400 V / 2.2kW	400 V 3 kW	PTO tractor	PTO + Elec. 400 V / 3 kW
Ø Flywheel (mm)	520	520	620	620	620	620	620	720	720	720
Height/width of cut (cm)	39/50	39/50	43/61	43/61	42/61	42/61	42/61	49/70	49/70	49/70
Dimension of table (cm)	78/68	78/68	97/80	97/80	97/80	97/80	97/80	97/80	97/80	97/80
Dimension (HxLxW cm)	202x100x68	202x100x68	217x120x83	217x120x83	217x130x80	217x130x80	217x130x80	237x125x85	236x135x80	236x135x80
Weight (kg)	200	200	260	260	269	285	285	320	318	334
Guidance trolley for model 620 and 720(SCI000510)										
Blade for band-saw 520 (30x0.6 lg 4300) (LAM00029)										
Blade for band-saw 620 (30x0.6 lg 4740) (LAM00030)										
Blade for band-saw 720 (30x0.6 lg 5200) (LAM00031)										
PTO shaft type 3 (CAR00001A)										