

Vertical splitter 9/12 tons - HV series

■ HV series

Available in 9/12 tons with two splitting speeds.

- 2-hand control
- Cylinder stroke 55 cm
- Inflatable wheels for easy moving
- Trail support included (*gasoline models*)
- Integrated phase inverter (400 V)
- Robust and durable design : welded frame
- Floor plate in full steel
- Brass slide rails



HVE12 MDP



Log holding arms



Ø 40 cm
< 60 cm >

Log splitter	HVE09 MSP	HVE09 MDP	HVE09 T	HVES09	HVE12 MSP	HVE12 MDP	HVE12 T	HVES12
Splitting force (to)	9	9	9	9	12	12	12	12
Splitting length (cm)	55	55	55	55	55	55	55	55
Pump	single	double	single	double	single	double	single	double
Power supply	230 V / 2,2 kW	230 V / 2,2 kW	400 V / 3 kW	petrol Honda 5,5 HP	230 V / 2,2 kW	230 V / 2,2 kW	400 V / 4 kW	petrol Honda 5,5 HP
Speed 1 (cm/s)	3,2	6,62	5,6	8,13	2,51	4,23	4,2	5,6
Speed 2 (cm/s)	7,74	14,8	13	18,86	6,22	10,07	11,5	14,61
Return speed (cm/s)	5,1	11,2	9,8	13,7	4,02	7,2	6,8	9,82
Oil tank capacity (L)	13	13	13	13	13	13	13	13
Pump output	7,5 L/min	18,6 L/min	13,5 L/min	19 L/min	7,5 L/min	18,6 L/min	16,5 L/min	19 L/min
Dimension (HxLxW cm)	162x76x100	162x76x100	162x76x100	162x76x230	162x76x100	162x76x100	162x76x100	162x76x230
Weight (kg)	206	200	200	220	210	211	205	230

Trail support (TIM000200)

400 V female plug (PRI00002)