

## WSA series 700 ED - 700 EC - 700 P - 700 PE - 700 Ess

- 3 wheels and carrying handle for easy handling
- TCT saw blade Ø 700 mm
- High quality painting
- Overload protection circuit breaker and safety limit switch on cover ( for electric motor )
- Emergency stop lever at PTO and gasoline version
- Ergonomic easy tilting
- Protective cover according to EN 1870-6 : 2017
- Adjustable cutting length indicator
- Wood holding arm during saw process
- Welded and reinforced frame
- Certified FN 1870-6





Mobility kit WSA not approved for road use



Tilting extension

Circular log carriage saw	WSA-700 ED	WSA-700 EC	WSA-700 P	WSA-700 PE	WSA-700 Ess
Power supply	Elec. 400 V 15.5 kW / 16 A direct drive	Elec. 400 V 7.5 kW / 16 A belt drive	PTO tractor belt drive	Elec. 400 V 7.5 kW / 16 A + PTO tractor belt drive	Briggs & Statton Ess OHV 9 HP belt drive
TCT blade Ø700/30 mm, 42 teeth	Standard	Standard	Standard	Standard	Standard
Ø max. round or splitted log (cm)	24	24	24	24	24
Electric motor speed (rpm)	1350	1350		1350	
Weight (kg)	142	162	175	220	188
Mobility kit with 2 big wheels and drawbar					
TCT blade Ø 700/30 mm, 42 teeth ( LAM00011 )					
PTO shaft Type 3 ( CAR00001A )					
Tilting extension					
400 V female plug ( PRI00002 )					

## SAWING RANGE









Folding handle and transport wheels



Log grip system locks the wood while sawing





Easy access to the saw blade