

5 m independant conveyor - TMB

SAWING RANGE

■ 5 m independant conveyor - TMB

Independant conveyor, ideal to transport wood or other materials.

- Horizontal folding of the conveyor for a safe transport *
- Draw bar for the trailer coupling
- Telescopic conveyor with safety grid and individual sections
(changeable separately in case of defect)



VIDEO ON
WWW.A-M-R.FR

Conveyor	Elec. 1-phased or 3-phased	Hydraulic tractor	Petrol engine
Width (cm) / length (m)	35 / 5	35 / 5	35 / 5
Conveyor speed (m/s)	0,6	Depending from tractor output	0,4 - 0,9
Engine power	0,75 kW	X	4 CV
Height of loading / unloading (cm)	60 / Min: 170 - Max: 300	60 / Min: 170 - Max: 300	60 / Min: 170 - Max: 300
Dimension of the funnel (cm)	70 x 40	70 x 40	70 x 40
Dimension of transport	100 x 260 x 120		
Weight (kg)	290	290	325
Hydraulic flow control for Hy-version (REG000100)			
Towing ring (ANN00010)			

NEW

Conveyor without frame : 3-phase - TSC 400 V

Conveyor without frame : Single-phase - TSC 230 V

Conveyor without frame : Hydraulic supply - TSC Hy

* Non-road use