

Vertical splitter 9 tons - FB509TF series

SPLITTING RANGE



■ FB509TF series

- Patented synchronized 2-hand control with wood holding claw
- Integrated phase inverter (400 V)
- Safety circuit breaker
- Big wheels for easy transporting
- Adjustable cylinder stroke up to 50 cm
- High return speed
- Fix splitting table
- Storage space on both sides
- Oil filter
- Robust and durable design




FB509TF
with fixed table and 2 removable baskets



Ø 45 cm
< 50 cm >



Synchronized handle control (patented)



3-point linkage as standard on power take-off model

Log splitter	FB509TF M	FB509TF T	FB509TF PDF	FB509TF ESS
Splitting force (to)	9	9	9	9
Splitting length (cm)	55	55	55	55
Pump	double	single	single	double
Power supply	230 V / 2,2 kW	400 V / 4 kW	PTO tractor	Petrol Honda 5,5 PS
Splitting speed (cm/s)	8,2	6,8	5,7	8,7
Return speed (cm/s)	9,4	15,2	15,2	12,5
Oil tank capacity (L)	10	10	10	10
Pump output (L/min)	19	16,5	14,7	19
Dimension (HxLxW cm)	130 x 60 x 84	130 x 60 x 84	130 x 60 x 107	130 x 60 x 109
Weight (kg)	177	191	191	184
Combined power. CONTACT US	Split wedge FB509 (ECL000401)			
	3-point linkage as option for other FB509TF (ATT00019)			
	400 V female plug (PRI00002)			